

C41 AND E32

ORDERING INFORMATION

7387-00 **C41** Automatic Level, complete with high-visibility fitted carrying case with shoulder strap, plumb bob, tool kit, lens cap, rain cover, and operation manual.

7385-65 **E32** Automatic Level, with same equipment as above.

For other accessories, see pages 82-86.
For level rods, see pages 44-47.
For tripods, see page 43.



7387-00
Accuracy: 1/4" at 200 ft.

C41 AUTOMATIC LEVEL (20x)

Compact, versatile and sturdy. These features, along with the ones below, make this level the ideal tool for builders.

- ◆ Achieve an accuracy of $\pm .013$ ft. in one mile of double-run leveling.
- ◆ The horizontal circle is easy to use, so you can quickly lay out and measure angles.



7385-65
Accuracy: 1/16" at 100 ft.

E32 AUTOMATIC LEVEL (22x)

A low-cost, tough, precision level that is resistant to exposure to the elements. The E32 allows fast, easy set-up, along with precise collimation and a reliable automatic compensator.

- ◆ Achieve an accuracy of $\pm .008$ ft. in one mile of double-run leveling.
- ◆ The endless tangent horizontal drive allows fast, precise operation—and you can use either your right or left hand!
- ◆ A collimator-type sight lets you quickly lock onto the target.
- ◆ Crisp, bright optics are easy to read; horizontal circle is graduated in degrees to 360°.

QUICK SPECS

Telescope	C41	E32
Image	Erect	Erect
Magnification	20x	22x
Field of View	1° 30' (2.6 ft. @ 100 ft.)	1° 25' (2.5 ft. @ 100 ft.)
Minimum Focus	3 ft.	1 ft.
Stadia Ratio	1:100	1:100
Compensator		
Setting Accuracy	0.5"	0.5"
Range	$\pm 12'$	$\pm 15'$
Leveling Accuracy (all models)—in 1.0km (1 mile) of double-run leveling		
Standard Deviation	$\pm .013$ ft.	$\pm .008$ ft.
Level Vial (all models)—circular		
Sensitivity	10' / 2mm	10' / 2mm